Medicine Transporters Type 2.5 MT, 4 MT, 8 MT

1- Walls •prefabricated insulated sandwich panels assembly •foam-in-place Polly-urethane (CFC free) •100 mm thickness, 48 kg/m3 density •color-coat hot dip galvanized steel white color •Polly-ethylene covered sheets to protect the panels during manufacturing process •0.6 -mm thick external & Internal cladding	•injected under high pressure & 70°c •fire retardant •double bend by roll-former to increase the stiffness •tongue & groove edges to fasten the panels together with steel cam action •locks on all panel edges •precisely located cam lock & steel encased pin •air tight sealed joints
2- Ceiling: • same material as wall panels	•0.6 pre-painted steel sheets for inner cladding
3- Floor: •same material as wall panels •12 mm treated ply-wood layer	•aluminum checkered plate covering the floor to afford heavy weights
4- Doors: •same specs of walls •bar locking system	•heavy-duty accessories •heavy duty gasket to assure tightness •270˚door opening angle for each leaf
5- Frame: • 1.25 mm stainless steel angles	•cage frame •heavy duty fastening to the truck chassis
6- Lighting: • inner low temperature lighting	•traffic signal lighting
• Suitable for rough roads • 1 or 2 shelves in each compartment • extra roof to provide shade for the compartment • Optional straps to tightly hold the medicine boxes	•single or multiple compartments •each compartment is completely isolated from others •easy loading and unloading of the truck •tilted floor for ease of cleaning

7-Sizes:

- **small:** 2.5 tons 3.10 X 1.70 X 1.70 mt (type 2.5MT)
- **medium:** 4 tons 4.35 X 2.10 X 2.00 mt (type 4MT)
- **large:** 8 tons 5.5 X 2.40 X 2.20 mt (type 8MT)

8- Cooling Units:

- Operates by truck engine & electric 3 phase suitable for tropical areas.
- Internal temperature adjustable from –20 to +10 optional thermograph. To provide an evidence for the temperature fluctuation versus time inside the Medicine compartment.

ELECTROLAB
212, Sudan St. Midan Lebanon Cairo – Egypt
www.electrolabtrucks.com

Tel.: ++20-2- 347 9769/ 347 4236
Fax: ++ 20-2-302 5791
Email:electrolab@electrolabtrucks.com